CH Corporation supplies attenuators with the electronic manufactuers. The attenuators are made with the state of the art manufacturing technology. There are Rectangular type attenuators and Round type ones. Also It can be made to meet customer' s requirements. Attenuation value can be custom made to be 10dB, 20dB, 30dB, 40dB, or 50dB. Also,. Attenuator power covers from 0.1 watt to 1,000 watt and frequency range is DC to 3GHz, 4GHz, 5GHz, 6GHz, and sometimes 12GHz. Just tell us "We need the attenuator meeting the spec:Average power 100 watt, Frequency range DC to 4GHz, Attenuation value 30dB, Rectangular type, and N Female to N Female connector .In the spec of attenuator, flatness and endurance are important. The flatness of the attenuator is very good. Endurance is over 50,000 hours. The IMD spec of the attenuator is around -100dBc in general. The temperature spec is -40℃ to 80℃. Impedance is 50Ω. The atenuators are used at many of reputable manufacturers around the world. These are your best choice.

Attenuator

P/N	Freq-uency	Power (Watt)	Attenuation Value	Con-nector	VSWR	Size (mm) & Weight	Drawing
SJSNG100003030N SJSNG100003040N	DC-3GHz	1,000	30dB 40dB	N-type	1.4	400x410x147	1
SJSN50003030N SJSN50003040N SJSN50004030N SJSN50004040N SJSN50005030N SJSN50005040N SJSN50006030N SJSN50006040N	DC-3GHz DC-4GHz DC-5GHz DC-6GHz	500	30dB 40dB 30dB 40dB 30dB 40dB 30dB 40dB	N-type	1.2 1.25	400X245X97mm, 10Kg	2
SJSN30003030N SJSN30003040N SJSN30004030N SNSN30004040N SJSN30005030N SJSN30005040N SJSN30006030N SJSN30006040N	DC-3GHz DC-4GHz DC-5GHz DC-6GHz	300	30dB 40dB 30dB 40dB 30dB 40dB 30dB 40dB	N-type	1.2 1.25	300X160X84mm, 5.8Kg	3
SJSNW20003030N SJSNW20003040N SJSNW20004030N SJSNW20004040N SJSNW20005030N SJSNW20005040N SJSNW20006030N SJSNW20006040N	DC-3GHz DC-4GHz DC-5GHz DC-6GHz	200	30dB 40dB 30dB 40dB 30dB 40dB 30dB 40dB	N-type	1.2 1.25	200X142X65mm, 2.4Kg	4
SJSN15003030N SJSN15003040N SJSN15004030N SJSN15004040N SJSN15005030N SJSN15005040N SJSN15006030N SJSN15006040N	DC-3GHz DC-4GHz DC-5GHz DC-6GHz	150	30dB 40dB 30dB 40dB 30dB 40dB 30dB 40dB	N-type	1.2 1.25	142X120X65mm, 1.9Kg	5

CH Corporation
(Samsungdong),(No. 3001, 30th Floor, Trade Tower), 511, Youngdong Daero, Gangnamku, Seoul, 135-729, KoreaTel:82-2-6000-3977 Fax:82-2-6000-3999 E-Mail:hsch@kita.net, chuhyang@kita.net
Website:www.chcorp.co.kr


P/N	Freq-uncy	Power	Attenuat-ion Value	Connector	VSWR	Size & Weight	Drawing
SJSNW10003030N	DC-3GHz	100	30dB	N-Type	1.15	120X100X60 mm, 1.2Kg	6
SJSNW10003040N			40dB				
SJSNW10004030N	DC-4GHz		30dB				
SJSNW10004040N			40dB				
SJSNW10005030N	DC-5GHz		30dB				
SJSNW10005040N			40dB				
SJSNW10006030N	DC-6GHz		30dB		1.2		
SJSNW10006040N			40dB				
SJSNL10003030N	DC-3Ghz	100	30dB	N-type	1.2	132X76X76mm, 1.45Kg	7
SJSNL10004040N	DC-4GHz		40dB				
SJSNL10005030N	DC-5GHz		30dB				
SJSNL10006040N	DC-6GHz		40dB		1.35		
SJSNL10008030N	DC-8GHz		30dB				
SJSNL100010040N	DC-10GHz		40dB		1.4		
SJSN8001230N	DC-1.2GHz	80	30dB	N-Type	1.2	100X85X60mm, 920g	8
SJSN8001240N	DC-1.2GHz		40dB				
SJSN80012530N	DC-1.25GHz		30dB		1.25		
SJSN80012540N	DC-1.25GHz		40dB				
SJRNZ5003030N	DC-3GHz	50	30dB	N-type	1.2	Ø45X143mm, 270g	9
SJRNZ5003040N			40dB				
SJRNZ5008030N	DC-8GHz		30dB		1.25		
SJRNZ5008040N			40dB				
SJRNZ50012430N	DC-12.4GHz		30dB		1.3		
SJRNZ50012440N			40dB				
SJRNZ50018030N	DC-18GHz		30dB		1.4		
SJRNZ50018040N			40dB				
SJRNO5003030N	DC-3GHz	50	30dB	N-type	1.2	Ø64X109mm, 420g	10
SJRNO5003040N			40dB				
SJRNO5004030N	DC-4GHz		30dB				
SJRNO5004040N			40dB				
SJRNO5005030N	DC-5GHz		30dB				
SJRNO5005040N			40dB				
SJRNO5006030N	DC-6GHz		30dB		1.25		
SJRNO5006040N			40dB				

CH Corporation
(Samsungdong),(No. 3001, 30th Floor, Trade Tower), 511, Youngdong Daero, Gangnamku, Seoul, 135-729, KoreaTel:82-2-6000-3977 Fax:82-2-6000-3999 E-Mail:hsch@kita.net, chuhyang@kita.net
Website:www.chcorp.co.kr


P/N	Freq-uency	Power (Watt)	Attenuat-ion Value	Con-nector	VSWR	Size & Weight	Drawing
SJSNW3003030N SJSNW3003040N SJSNW3004030N SJSNW3004040N SJSNW3005030N SJSNW3005040N SJSNW3006030N SJSNW3006040N	DC-3GHz DC-4GHz DC-5GHz DC-6GHz	30	30dB 40dB 30dB 40dB 30dB 40dB 30dB 40dB	N-type	1.2 1.25	60x60x 60mm, 402g	11
SJRNG3003030N SJRNG3003040N SJRNG3004030N SJRNG3004040N SJRNG3005030N SJRNG3005040N SJRNG3006030N SJRNG3006040N	DC-3GHz DC-4GHz DC-5GHz DC-6GHz	30	30dB 40dB 30dB 40dB 30dB 40dB 30dB 40dB	N-type	1.2 1.25	Ø45X1 09mm, 245g	12

CH Corporation
(Samsungdong),(No. 3001, 30th Floor, Trade Tower), 511, Youngdong Daero, Gangnamku, Seoul, 135-729, KoreaTel:82-2-6000-3977 Fax:82-2-6000-3999 E-Mail:hsch@kita.net, chuhyang@kita.net
Website:www.chcorp.co.kr

DRAWING 1.




DRAWING 2






CH Corporation
(Samsungdong),(No. 3001, 30th Floor, Trade Tower), 511, Youngdong Daero, Gangnamku, Seoul, 135-729, KoreaTel:82-2-6000-3977 Fax:82-2-6000-3999 E-Mail:hsch@kita.net, chuhyang@kita.net Website:www.chcorp.co.kr

DRAWING 3.






DRAWING 4.






CH Corporation
(Samsungdong),(No. 3001, 30th Floor, Trade Tower), 511, Youngdong Daero, Gangnamku, Seoul, 135-729, KoreaTel:82-2-6000-3977 Fax:82-2-6000-3999 E-Mail:hsch@kita.net, chuhyang@kita.net Website:www.chcorp.co.kr

DRAWING 5.




Drawing 6.



CH Corporation
(Samsungdong),(No. 3001, 30th Floor, Trade Tower), 511, Youngdong Daero, Gangnamku, Seoul, 135-729, KoreaTel:82-2-6000-3977 Fax:82-2-6000-3999 E-Mail:hsch@kita.net, chuhyang@kita.net Website:www.chcorp.co.kr




DRAWING 7






DRAWING 8.



CH Corporation
(Samsungdong),(No. 3001, 30th Floor, Trade Tower), 511, Youngdong Daero, Gangnamku, Seoul, 135-729, KoreaTel:82-2-6000-3977 Fax:82-2-6000-3999 E-Mail:hsch@kita.net, chuhyang@kita.net Website:www.chcorp.co.kr




DRAWING 9






DRAWING 10.



CH Corporation
(Samsungdong),(No. 3001, 30th Floor, Trade Tower), 511, Youngdong Daero, Gangnamku, Seoul, 135-729, KoreaTel:82-2-6000-3977 Fax:82-2-6000-3999 E-Mail:hsch@kita.net, chuhyang@kita.net Website:www.chcorp.co.kr




Drawing 11





CH Corporation
(Samsungdong),(No. 3001, 30th Floor, Trade Tower), 511, Youngdong Daero, Gangnamku, Seoul, 135-729, KoreaTel:82-2-6000-3977 Fax:82-2-6000-3999 E-Mail:hsch@kita.net, chuhyang@kita.net Website:www.chcorp.co.kr

DRAWING 12





Delivery :3-4Weeks ARO
P/N AB: Rectangular type Attenuator
AR Round Type Attenuator
Attenuation: 1-50dB (Custom spec is available)
For details, please contact CH Corporation
Product quality is assured for a year.

CH Corporation
(Samsungdong),(No. 3001, 30th Floor, Trade Tower), 511, Youngdong Daero, Gangnamku, Seoul, 135-729, KoreaTel:82-2-6000-3977 Fax:82-2-6000-3999 E-Mail:hsch@kita.net, chuhyang@kita.net Website:www.chcorp.co.kr